

Omnisports

HETEROGENEOUS VINYL

Let's
play



CONTENTS

OMNISPORTS – ENJOY PLAYING, FEEL SECURE	4
SPORTS SURFACE - STANDARDS EN 14904	6
INSPIRATIONS	7
OMNISPORTS VINYL FLOORING SOLUTIONS - TO MEET ALL YOUR NEEDS	8
PLAY IN A HEALTHIER ENVIRONMENT	10
OMNISPORTS CARES ABOUT INDOOR AIR QUALITY	10
PLAY SAFER	11
PERFORM WITH PLEASURE AND COMFORT	12
EASY & DURABLE	14
GREENLAY UNIQUE INSTALLATION METHOD	15
THE OMNISPORTS COLLECTION:	
COMPACT	16
SPEED	17
TRAINING	18
REFERENCE <i>MULTI-USE</i>	19
ACTIVE	20
EXCEL	21
PUREPLAY	22
SPECIALITIES: DANCEFLOOR/ BADMINTON KIT/ TABLE TENNIS	23
INSTALLATION INSTRUCTIONS	24
ACCESSORIES FOR INSTALLATION & FINISHING	25
MAINTENANCE INSTRUCTIONS	26
PROTECTION & COMPLEMENTARY SOLUTIONS	27
TECHNICAL SPECIFICATIONS	28
TARKETT SERVICES TO MEET ALL OF YOUR EXPECTATIONS	29



Let's play

OMNISPORTS HETEROGENEOUS VINYL

Omnisports provides ideal innovative floorings for young athletes and children. For them, performance and pleasure should be their only concern. Omnisports floorings meet the highest environmental and health standards allowing sports to be played in stimulating and safe surroundings.

OMNISPORTS

ENJOY PLAYING, FEEL SECURE



Healthier & safer environment

PLAY IN A HEALTHIER ENVIRONMENT

- Contribute to friendly sports spaces:



- Contribute to lung protection thanks to **extremely low VOC emissions**.

PLAY SAFER

- Minimize the risk of injury with integrated cushion backing.
- Provide shock absorption levels for all ages, weights and levels of play.



Higher performance & versatility

Choose the right product for your facility, from practice in schools to competition level.

- Enhance sports performance* thanks to **good energy return**.
- Guarantee **an adequate & consistent level of ball bounce** for handball, basketball, volleyball and other sports.
- Accomodate **non-sporting events** while providing **ideal performance for sports practice**.
- Provide a **better grip** for control when sliding.
- **Reduce fatigue** throughout sports practice.

*Except for Omnisports Compact



More comfort & pleasure

- Guarantee **good underfoot comfort**.
- Reduce noise levels thanks to **cushion vinyl acoustic**.
- Allow for personalized installations with a choice of

24 colours



- Boost children's energy levels with **vibrant colours**.



Easy to maintain, durable & sustainable

Appreciate resistance to:

- Stains & scratches.
- Indentation marks.
- Rolling load.

■ Reduce maintenance costs



TopClean XP engineered surface treatment.

■ Choose **GREENLAY**

Unique Installation Method:

Extremely **convenient and sustainable**:

20% faster

98% adhesive free

easy removal



SPORTS SURFACE

STANDARDS EN 14904

The EN 14904 standard is the basis of the EC marking for indoor sports surfaces. This standard is mandatory and specifies certain requirements for Multi-Use sports surfaces in indoor facilities. The standard guarantees a safe and adapted surface for sports performance and comfort, as well as a durable and resistant flooring throughout its lifespan.


Requirements for safety in use	Standards	Requirements
Shock absorption	EN 14808	≥ 25%
Friction	EN 13036-4	80-110
Vertical deformation	EN 14809	≤ 5mm

Technical requirements	Standards	Requirements
Vertical ball behaviour	EN 12235	≥ 90%
Resistance to a rolling load	EN 1569	≤ 0.5mm
Resistance to wear	EN ISO 5470-1	< 1g
Reaction to fire	EN 13501-1	According to standard
Resistance to indentation	EN 1516	< 0.5mm
Resistance to impact	EN 1517	< 0.5mm
Formaldehyde emission and content of pentachlorophenol	EN 717-1 EN 717-2	Declaration
Specular reflectance	EN 13745	According to standard
Specular gloss	EN ISO 2813	≤ 30% at 85° angle

They certified Tarkett Omnisports



INSPIRATIONS




OMNISPORTS VINYL FLOORING SOLUTIONS

TO MEET ALL YOUR NEEDS

- Highly recommended
- ★ Highly recommended with Lumaflex sub-construction
- Suitable
- ★ Except electric wheelchairs

	Omnisports									
	EN 14904									
	Pureplay	Excel	Active	Reference Multi-Use	Training	Speed	Compact	Badminton Kit	Table tennis	Dancefloor
Multi-sports	■	■	■	■						
Multi-Use				■			★			
Basketball	■	■	■	■						
Volley-ball	■	■	■	★						
Handball	■	■	■	★						
Futsal	■	■	■	■						
Table tennis				■	■				■	
Badminton	■	■	■	■				■		
Fitness - aerobics			■	■	■					
Fitness - cardio (bikes, tradmills, rowing machines,...)					■	■	■			
Wellness centers				■	■	■				
Roller sports and handisports			★				★			
Dance										■
Traffic areas (corridors, entrance halls, meeting rooms,...)							■			

Sports Flooring
(EN 14904 CERTIFIED)



To comply with the EN standard, Omnisports Compact, Speed and Training must be combined with a Lumaflex subconstruction.

PLAY IN A HEALTHIER ENVIRONMENT

Indoor air quality is essential for the health of athletes and especially children who are exposed to higher risk of indoor pollution to immature lungs.

Exposure risk with indoor pollution



WITHOUT sports activity



ATHLETES during sports activity



CHILDREN during sports activity

OMNISPORTS CARES ABOUT INDOOR AIR QUALITY

OMNISPORTS CONTAINS NO PHTHALATES

In 2009, Tarkett launched the **first vinyl flooring range with phthalate free technology**, designed with renewable plasticizers which are also used in the children's toy industry.

phthalate-free
100%

OMNISPORTS MINIMIZES THE RISK OF RESPIRATORY DISEASE THANKS TO EXTREMELY LOW VOC EMISSIONS

All Tarkett Sports floors contribute to better air quality with under $10\mu\text{g}/\text{m}^3$ TVOC emissions (after 28 days) - 100 times lower than standard levels.

VOC EMISSIONS
10 TIMES LOWER
THAN SIMILAR PRODUCTS

TVOC (AFTER 28 DAYS)
100 TIMES LOWER
THAN STANDARD REQUIREMENTS

OMNISPORTS REDUCES POLLUTANT EFFECT THANKS TO 98% ADHESIVE FREE UNIQUE INSTALLATION METHOD

Greenlay® installation method is unique and convenient, improving air quality with minimum use of adhesive. (Please refer to page 15).

98%
adhesive-free

PLAY SAFER

Protecting players is our first concern. Omnisports provides different levels of shock absorption, impact deflection, friction and playing characteristics adapted to the different ages, weights and skill levels of sports users.

- Omnisports minimizes the risk of injury and fall impact.
- Homogeneous Omnisports embossed surface and treatment* contributes to limiting friction burn risks and provides safer protection with anti-slip grip on all patterns and colours.

Shock absorption levels vary according to players' weight



NON EN 14904 CERTIFIED
<25%
SHOCK ABSORPTION

OMNISPORTS EN 14904 CERTIFIED**
≥25%
SHOCK ABSORPTION

- Highly cellularized foam underlayer that absorbs pressure at impact.
- Specific surface treatment embossing.

*Except Dancefloor.


**Omnisports Reference Multi-Use, Active, Excel & Pureplay.

PERFORM WITH PLEASURE AND COMFORT

Tarkett's range of point elastic sports flooring is designed to adapt to the needs of all athletes from leisure to high level performance requirements.

NEW SOLUTIONS FOR MULTI-USE FACILITIES

Omnisports Reference *Multi-Use* 6,1 mm is the ideal flooring for basketball, volleyball, and many other sports, while at the same time easily accommodating non-sporting events.



- P1 level shock absorption ≥ 25%.
- Exceptional resistance to indentation ≤ 0.1mm.
- Available with Greenlay unique installation method.

(Please refer to page 15.)

Acoustic reduction and comfort



Uniformly reactive surface for consistent ball bounce.



Helps reduce the risk muscle fatigue.



Helps reduce risk of joint erosion.



Boost players energy levels with vibrant colours.



Good energy return.



Good underfoot comfort.



Better grip control when sliding to support sport movement.



EASY & DURABLE

EASY TO MAINTAIN

Omnisports floorings are highly resistant, designed to provide durable surfaces and to reduce maintenance costs.

- Unique product construction with solid, heavy and dense calendared sheet: resistant surface to indentation and impact.
- Engineered TopClean XP surface treatment for easier and ecological maintenance: reduced water and chemical agent consumption.



EXCEPTIONAL RESISTANCE TO INDENTATION MARKS AND ROLLING LOAD



REDUCED MAINTENANCE COSTS



EASY MAINTENANCE





RESISTANT TO STAINS AND SCRATCHES



Unique 2m roll width

30% less welding required, decreasing the areas at risk of soiling



GREENLAY UNIQUE INSTALLATION METHOD

Greenlay is a sustainable loose-lay installation method - only 2% of the surface is glued - offering an economical and easy installation solution. This unique method is made possible by:

- The product's exceptional dimensional stability (0.10%)
- Omnisports reference *Multi-Use*, *Active*, *Excel* & *Pureplay*
- The honeycomb backing, creating a suction effect

98% adhesive-free

Compliant & efficient

- EN 14904 compliant
- Over 1 million m² installed over 20 years
- 10 year warrantied installation method

Convenient & practical


- Easy access to subfloor after installation with no damage to the subfloor
- Resistance to rolling load

Quick & easy to use

- Reduced installation time by 20%
- Immediate setting in traffic

Answering jobsites needs


- Resistance to rising moisture (up to 10% CCM)
- Compatible with heated subfloor





COMPACT

2 MM



IDEAL FLOORING FOR TRAFFIC AREAS

- High mechanical resistance to indentation: 0.10mm.
- Easy circulation of rolling loads.
- Suitable for installation with Lumaflex sub-construction: area-elastic system, ideal for light multi-use purposes.

Recommended applications:

Traffic areas: corridors, lockers*, entrance halls, meeting rooms, cardio (bikes, treadmill, rowing machines...) etc.



- 1 Adequate balance of friction and grip control. Specific engineered surface embossing.
- 2 Very high resistance to scratches and easy maintenance. **TopClean XP™ treatment.**
- 3 Exceptional resistance to wear. Pure transparent vinyl wear layer.
- 4 Dynamic colours and realistic decors. High definition printing for a perfect wood surface appearance and built-in units for higher colour intensity.
- 5 Superior dimensional stability (<0.10%). Unwoven glass fibre.
- 6 High resistance to indentation and tearing. Solid Homogeneous calendared sheet made of recycled vinyl.

CHOOSE YOUR COLOURS




«ROLL LENGTH» ON DEMAND available, minimum quantity: 550m² on global order.
«CUT SERVICE» available.

● ON DEMAND available, minimum quantity: 700m² (+/- 10%).

*Without direct access to wetrooms.

SPEED

3,45 MM



IDEAL FOR WALKING AND ACOUSTIC COMFORT IN FITNESS, LEISURE AND WELLNESS AREAS

- Walking and acoustic comfort.
- Good resistance to indentation and rolling loads.
- Suitable for installation with Lumaflex sub-construction: combined-elastic system, ideal for multi-sports facilities.

Recommended applications:

Fitness, wellness centres, boxing, etc.



- 1 Adequate balance of friction and grip control. Specific engineered surface embossing.
- 2 Very high resistance to scratches and easy maintenance. **TopClean XP™ treatment.**
- 3 Exceptional resistance to wear. Pure transparent vinyl wear layer.
- 4 Dynamic colours and realistic decors. High definition printing for a perfect wood surface appearance and built-in units for higher colour intensity.
- 5 Superior dimensional stability (<0.10%). Unwoven glass fibre.
- 6 High resistance to indentation and tearing. Solid Homogeneous calendared sheet made of recycled vinyl.
- 7 Comfort, safety and sound reduction. High-density closed-cell foam with engineered honeycomb backing.

CHOOSE YOUR COLOURS



«ROLL LENGTH» ON DEMAND available, minimum quantity: 550m² on global order.
«CUT SERVICE» available.


○ ON DEMAND available, minimum quantity: 700m² (+/- 10%).



P1
Sports performance and Multi-Use resistance

TRAINING

5 MM



IDEAL FOR SMALL SPORTS FACILITIES AND LEISURE AREAS

- Good shock absorption level: 17%.
- Walking and acoustic comfort.
- Suitable for installation with Lumaflex sub-construction: combined-elastic system, ideal for multi-sports facilities.

Recommended applications:

Fitness, wellness centres, yoga, aerobics, boxing, rehabilitation centres, etc.



- 1 Adequate balance of friction and grip control. Specific engineered surface embossing.
- 2 Very high resistance to scratches and easy maintenance. **TopClean XP™** treatment.
- 3 Exceptional resistance to wear. Pure transparent vinyl wear layer.
- 4 Dynamic colours and realistic decors. High definition printing for a perfect wood surface appearance and built-in unis for higher colour intensity.
- 5 Superior dimensional stability (<math><0.10\%</math>). Unwoven glass fibre.
- 6 High resistance to indentation and tearing. Solid Homogeneous calendered sheet made of recycled vinyl.
- 7 Comfort, safety and sound reduction. High-density closed-cell foam with engineered honeycomb backing.

CHOOSE YOUR COLOURS



«ROLL LENGTH» ON DEMAND available, minimum quantity: 550m² on global order.

«CUT SERVICE» available.


● ON DEMAND available, minimum quantity: 700m² (+/- 10%).

REFERENCE MULTI-USE

6,1 MM

NEW

NEW!
FOAM BACKING: **XCS**
(EXTREMELY DENSE CELLULAR STRUCTURE).



IDEAL FLOORING FOR MULTI-SPORTS PRACTICE AND NON-SPORTING EVENTS

- P1 level shock absorption: $\geq 25\%$.
- Exceptional resistance to static loads (chairs, tables, bleachers,...) : $\leq 0.10\text{mm}^*$.
- Superior resistance to heavy rolling loads (trolleys...).
- Resistance to stains and scratches: 0,70mm PU reinforced wearlayer.
- Available with Greenlay unique installation method: 98% adhesive-free**.

Recommended applications:

Multi-sports (basketball, volley-ball, handball, badminton...) and non sporting events (exams, elections, balls, public meetings, associative meetings...).



- 1 Adequate balance of friction and grip control. Specific engineered surface embossing.
- 2 Very high resistance to scratches and easy maintenance. **TopClean XP™** treatment.
- 3 Exceptional resistance to wear. Pure transparent vinyl wear layer.
- 4 Dynamic colours and realistic decors. High definition printing for a perfect wood surface appearance and built-in unis for higher colour intensity.
- 5 Superior dimensional stability (<math><0.10\%</math>). Unwoven glass fibre.
- 6 High resistance to indentation and tearing. Solid homogeneous calendered sheet made of recycled vinyl.
- 7 Comfort, performance and sound reduction.

CHOOSE YOUR COLOURS



NEW! XCS foam, extremely dense cellular structure for excellent recovery.

«ROLL LENGTH» ON DEMAND available, minimum quantity: 550m² on global order.

«CUT SERVICE» available.

*Chair with 80kg person during 5h.

**See page 15.



ACTIVE

7,1 MM


NEW

AFFORDABLE MULTI-SPORTS VINYL SOLUTION FOR SCHOOL USE

- Good shock absorption level: 28%*.
- Uniformly reactive surface for consistent ball bounce.
- Good underfoot comfort.
- Resistance to stains and scratches: 0,70mm PU reinforced wearlayer.
- Available with Greenlay unique installation method: 98% adhesive-free**.

Recommended applications:

Multi-sports: Team: volley-ball, handball, badminton, basketball, futsal... and individual - tai chi, gymnastics...



- 1 Adequate balance of friction and grip control. Specific engineered surface embossing.
- 2 Very high resistance to scratches and easy maintenance. **TopClean XP™ treatment.**
- 3 Exceptional resistance to wear. Pure transparent vinyl wear layer.
- 4 Dynamic colours and realistic decors. High definition printing for a perfect wood surface appearance and built-in units for higher colour intensity.
- 5 Superior dimensional stability (<math><0.10\%</math>). Unwoven glass fibre.
- 6 High resistance to indentation and tearing. Solid Homogeneous calendared sheet made of recycled vinyl.
- 7 Comfort, safety and sound reduction. High-density closed-cell foam with engineered honeycomb backing.

CHOOSE YOUR COLOURS



«ROLL LENGTH» ON DEMAND available, minimum quantity: 550m² on global order.
«CUT SERVICE» available.

*Average measured value.
**See page 15.

EXCEL


8,3 MM

COMFORT AND SPORTS PERFORMANCE

- Superior shock absorption level: 30%*.
- Uniformly reactive surface for consistent ball bounce.
- Approved by international sports federations: IHF (handball), FIBA (basketball).
- Resistance to stains and scratches: 0,70mm PU reinforced wearlayer.
- Available with Greenlay unique installation method: 98% adhesive-free**.


Recommended applications:

school use, handball (up to competition level), basketball (up to competition level), badminton, volley-ball, futsal etc.



- 1 Adequate balance of friction and grip control. Specific engineered surface embossing.
- 2 Very high resistance to scratches and easy maintenance. **TopClean XP™ treatment.**
- 3 Exceptional resistance to wear. Pure transparent vinyl wear layer.
- 4 Dynamic colours and realistic decors. High definition printing for a perfect wood surface appearance and built-in units for higher colour intensity.
- 5 Superior dimensional stability (<math><0.10\%</math>). Unwoven glass fibre.
- 6 High resistance to indentation and tearing. Solid Homogeneous calendared sheet made of recycled vinyl.
- 7 Comfort, safety and sound reduction. High-density closed-cell foam with engineered honeycomb backing.

CHOOSE YOUR COLOURS



«ROLL LENGTH» ON DEMAND available, minimum quantity: 550m² on global order.
«CUT SERVICE» available.

*Average measured value.
**See page 15.



SPORTS FLOORING
(EN 14904 CERTIFIED)

P2
Extreme protection, comfort and performance

≥25% SHOCK ABSORPTION

PUREPLAY


9,4 MM

EXTREME PROTECTION, COMFORT AND SPORTS PERFORMANCES

- Optimized cushion-vinyl construction: 6,5mm foam for excellent shock absorption ≥35% (P2 classified).
- Underfoot comfort, adapted to children with direct contact to the floor.
- Playing comfort for athletes.
- Excellent acoustic performance.
- Resistance to stains and scratches; 0,80mm PU reinforced wearlayer.
- Approved by international sports federations: IHF (handball), FIBA (basketball).
- Available with Greenlay unique installation method: 98% adhesive-free*.

Recommended applications:

City sportshalls with multi-sports usages: basketball (up to competition level), handball, volley-ball, etc.



- 1 Adequate balance of friction and grip control. Specific engineered surface embossing.
- 2 Very high resistance to scratches and easy maintenance. **TopClean XP™ treatment.**
- 3 Exceptional resistance to wear. Pure transparent vinyl wear layer.
- 4 Dynamic colours and realistic decors. High definition printing for a perfect wood surface appearance and built-in units for higher colour intensity.
- 5 Superior dimensional stability (<math><0.10\%</math>). Unwoven glass fibre.
- 6 High resistance to indentation and tearing. Solid Homogeneous calendared sheet made of recycled vinyl.
- 7 Comfort, safety and sound reduction. High-density closed-cell foam with engineered honeycomb backing.

CHOOSE YOUR COLOURS



«ROLL LENGTH» ON DEMAND available, minimum quantity: 550m² on global order.
«CUT SERVICE» available.

*See page 15.

SPECIALITIES

DANCEFLOOR

3,45 MM




THE IDEAL SOLUTION FOR DANCE STUDIOS PROFESSIONAL AND AMATEUR CLASSIC BALLET

- Excellent grip.
- Reduced risk of injury.
- Increased performance.



ON STOCK



BADMINTON KIT

3,45 MM



READY TO USE ROLLS FOR BADMINTON PRACTICE

- To be layed over existing flooring.
- Covers confusing existing game lines for optimal badminton practice experience.



KIT OF 2 ROLLS OF 33LM

- 1 Adequate balance of friction and grip control. Specific engineered surface embossing (except for Dancefloor).
- 2 Very high resistance to scratches and easy maintenance. **TopClean XP™ treatment.**
- 3 Exceptional resistance to wear. Pure transparent vinyl wear layer.
- 4 Dynamic colours and realistic decors. High definition printing for a perfect wood surface appearance and built-in units for higher colour intensity.
- 5 Superior dimensional stability (<math><0.10\%</math>). Unwoven glass fibre.
- 6 High resistance to indentation and tearing. Solid Homogeneous calendared sheet made of recycled vinyl.
- 7 Comfort, safety and sound reduction. High-density closed-cell foam with engineered honeycomb backing.

TABLE TENNIS

3,45 MM



TEXTURED SPORTS SURFACE IDEAL TABLE TENNIS PRACTICE

- Balanced grip thanks to textured surface with specific embossing.
- Superior resistance to indentation marks: tables...
- Underfoot comfort.




«ROLL LENGTH» ON DEMAND
Minimum quantity 550m² (on global order)

INSTALLATION


instructions

Our Omnisports floorings require minimal maintenance and according to EN 14904 tests, offer increased adhesion regardless of whether its surface is clean or dusty.



SUBFLOOR INSTALLATION: POSSIBLE OPTIONS

TYPE OF INSTALLATION	ACRYLIC GLUED	ACRYLIC GLUED ON TARKOLAY (VAPOUR BARRIER)	PU GLUED ON TARKOLAY (VAPOUR BARRIER)	LOOSE-LAID - GREENLAY
----------------------	---------------	--	---------------------------------------	-----------------------



	COMPATIBLE PRODUCTS	All Omnisports			Omnisports Reference Multi-Use, Active, Excel, Pureplay
	Concrete	Respecting local standards*	< 7%	< 10%	< 10%
Andhydrite	< 0.5%	< 1%	< 1.5%	< 0.5%	
Asphalt coated	Dry	Dry	Dry	Dry	
Bitumen coated	×	Dry	Dry	×	
Compatible with heating subfloor	✓	✓	✓	✓	
Accessibility to subfloor	×	×	×	✓	
Recyclability	×	×	×	✓	
Immediate usage after installation	×	×	×	✓	
Warranty	10 years	10 years	10 years	10 years	

Providing that the subfloor respects local standards. For detailed information please refer to complete installation guides.
*Non exposed to rising moisture.

ACCESSORIES

for installation & finishing

INSTALLATION ACCESSORIES



GREENLAY® GLUE
Dual-components (A+B)
1 pot of 5kg each

COMPONENT	ARTICLE CODE
A	1551057
B	1551058



GREENLAY® TARKOTAPE
Double-sided adhesive for Greenlay® installation
1 box of 12 rolls
1 roll: 152.4mm x 321m

ARTICLE CODE
1551082



DOUBLE-TAPE UNROLLER FOR TABLE TENNIS SOLUTION

ARTICLE CODE
1430002*



TARKOLAY UNDERLAYER
Moisture barrier for wet substrates creating natural ventilation
Thickness: 1.3mm

ARTICLE CODE
3960001

FINISHING ACCESSORIES



VINYL SKIRTINGS
1 box of 20 pcs - 51.401m
60mm high x 15mm wide x 2570mm long

ARTICLE CODE	COLORS
1551064	Beech
1446007	Black
1446009	Grey
1551062	Maple
1551063	Oak
1446018	Red
1551061	Royal blue
1551059	Sky blue



THRESHOLD STRIPS
Aluminium transition strips (4 sizes)
60 or 80mm wide : 1 box of 10 pcs - 301m
100 or 130mm wide : 1 box of 5 pcs - 151m
5mm high x 3000mm long

ARTICLE CODE	CHARACTERISTICS
1551078	60mm wide
1551079	80mm wide
1551080	100mm wide
1551081	130mm wide



ADAPTABLE TRANSITION STRIPS
Aluminium adaptable transition strip
Compensating up to 14mm difference in level
1 box of 10 pcs - 271m
41mm high x 2700mm long

ARTICLE CODE
1551071

VENTILATED SKIRTING FOR GREENLAY & TARKOLAY INSTALLATION

COLORS	ARTICLE CODE
Oak varnished	1551065


COLOUR NAME	LRV N°	NCS N°	WELDING RODS	
			Ø 4mm N° (Omnisports Speed & Compact)	Ø 5mm N° (Omnisports Training, Reference Multi-Use, Active, Pureplay)
UNI MINT GREEN	17	S4040-G	1287425	1285365
UNI NIGHT BLUE	12	S4050-R90B	1287918	1285029
UNI ORANGE	35	S1070-Y60R	1287139	1285139
UNI PURPLE	11	S4050-R40B	1287922	1285027
UNI RED	16	S2570-B40G	1291808	1285808
UNI ROYAL BLUE	10	S5040-R90B	1291367	1285367
UNI TEAL	18	S2555-B40G	1287317	1285015
UNI YELLOW	44	S1060-Y10R	1287315	1285013
UNI CORAL	21	S 2060-Y90R	1287920	1285633
UNI LAGOON	42	S 2030-B50G	1287919	1285195

COLOUR NAME	LRV N°	NCS N°	WELDING RODS	
			Ø 4mm N° (Omnisports Speed & Compact)	Ø 5mm N° (Omnisports Training, Reference Multi-Use, Active, Pureplay)
UNI LIME	57	S 1060-G80Y	1287924	1285122
CLASSIC OAK	25	S 3040-Y30R	1287318	1285016
BEECH	30	S 3020-Y30R	1291363	1285363
DARK BEECH	9	S 7020-Y70R	1287478	1285032
GOLDEN MAPLE	36	S 2030-Y30R	1291368	1285368
LIGHT MAPLE	52	S 1010-Y20R	1291681	1285031
MAPLE RED	16	S2570-Y90R	1291808	1285808
MAPLE GREY	20	S5500-N	1287183	1285183
MAPLE MINT GREEN	17	S5040-B80G	1287425	1285365
MAPLE SKY BLUE	20	S2050-R90B	1287926	1285035

*Special, no stock.

MAINTENANCE

instructions



Omnisports sports surfaces are treated with TopClean XP™. It's a UV-reticulated polyurethane surface treatment, which offers excellent resistance to wear and tear due to daily sports practice.

GENERAL ADVICE

- Installation of doormats at the entrance of the gymnasium to catch humidity, dirt, dust etc. They must be at least 3 strides long (approx. 1.5m).
- Usage of appropriate shoes: white soles dedicated to indoor sports practice.
- Non sporting events (exhibitions, concerts, dinners...) in sports hall: sports flooring protection required. (please see p.19 for detailed information about our Protection solutions).
- Heavy rolling load (trolleys, forklift etc): sports flooring protection required - across all the rolling area by using double layer of plywood (19mm).
- Always follow manufacturers' recommendations (detergent, cleaning machine...).

SETTING IN TRAFFIC	Actions	Instructions
--------------------	---------	--------------

	1. Removing dust and gravel	- Dry cleaning - Vacuum cleaning
	2. Cleaning	- Mechanical cleaning with scrubbing machine - red pad, medium speed- and water vacuuming, or combined machine - Use neutral detergent (pH 7/8) or alkaline detergent (pH 8/10) in case of heavy soiling - If an alkaline detergent (pH 8/10) is used, the flooring should be rinsed with water and water vacuumed
	3. Stain removal	- A detergent should be used to remove work site stains (glue, paint...) according to the nature of the stain - Do not use abrasive pads

DAILY CLEANING	Actions	Instructions
----------------	---------	--------------

	1. Removing dust and gravels	- Dry cleaning - Vacuum cleaning
	2. Cleaning (if and where it's necessary)	- With flat or micro fibre mop, impregnated or not or - with a combined machine (red pad, medium speed) or - with a rotocleaner - Use neutral detergent (pH 7/8)
	3. Stain removal	- For stubborn stains on the floor (for example handball players' resin) on goal posts, on seats etc.: use an alkaline detergent (pH 13/14) dilution 20% in spray, let it work during 1 minute and sweep with a white clean cloth

PERIODICAL CLEANING	Actions	Instructions
---------------------	---------	--------------


	1. Light soiling	- Machine cleaning: use a scrubbing machine fitted out with white soft brushes or red pads at medium speed or use rotocleaner - Use detergent neutral or alkaline (pH 7/9) with a 1% dilution
	2. Heavy soiling	- Machine cleaning: use a scrubbing machine fitted out with white soft brushes or red pads at medium speed, or use rotocleaner - Use alkaline detergent (pH 13) with a 10% dilution - Apply the mix without vacuuming and let it soak into the floor for 5 minutes and then vacuum the surface - In case of chalky white marks, rinse with clear water
	3. Stain removal	- For stubborn stains on the floor (for example handball players' resin) on goal posts, on seats etc.: use an alkaline detergent (pH 13/14) dilution 20% in spray, let it work during 1 minute and sweep with a white clean cloth
	4. Gloss restoration (exceptional)	- In areas where gloss/varnish has been worn, use buffing machine - white pad, high speed Please call technical services before to make sure this won't affect the sports characteristics of your surface

PROTECTION



PROTECTILES
Textile protection tiles
1 box of 10 pcs – 20m²
total weight: 3.1kg/m²
total thickness: 5.2mm
1m x 2m

COLORS	ARTICLE CODE
Blue	2490000
Grey	2490001
Brown	2490002
Night blue	44003003
Red	44003004
Green	44003005
Orange	44003006



TOUCHDOWN
PVC floor protection
total weight: 1.8kg/m²
total thickness: 1.3mm
2m x 10-40lm

COLORS	ARTICLE CODE
Grey	3964001
Beige	3964002
Green	3964003



TROLLEY FOR PROTECTILES
4 articulated wheels with rubber strips and 2 brakes
capacity: 100 Protectiles

ARTICLE CODE
1568001




UNROLLER FOR TOUCHDOWN
2 elements kit

ELEMENT (A) device	ARTICLE CODE
(B) chuck	1562001
	1562002

COMPLEMENTARY SOLUTIONS

WALL PROTECTION: PROTECTWALL



ProtectWall 1.5

Economical, design and resistant wall protection solution:

- 37 exclusive and matching designs & colours with Omnisports
- Protects walls against shocks and impacts - no reparation costs
- Easy maintenance thanks to TopClean XP surface treatment
- High flexibility for easy installation
- Full accessories package for perfect finish

FULL SOLUTION FOR WET AREAS: WETROOM CONCEPT



Granit Multisafe



Aquarelle Wall HFS



Integrated watertight and hygienic system including:

Slip resistant floorings:

- Homogeneous vinyl (Optima Multisafe, Granit Multisafe, Granit Safe.T)
 - Heterogeneous vinyl (Multisafe Aqua)
- Coordinated heterogeneous vinyl wall covering (Aquarelle Wall HFS)

Full range of accessories for perfect finish (welding rods, coving, drains, thresholds, pipe collars)

TECHNICAL SPECIFICATIONS

TECHNICAL DATA	STANDARD	COMPACT	SPEED	TRAINING	REFERENCE MULTI-USE	ACTIVE	EXCEL	PUREPLAY
CERTIFICATION & CLASSIFICATION								
Type of floor covering	EN 14041	Heterogeneous compact indoor floorcoverings	Heterogeneous indoor floorcoverings	Heterogeneous indoor floorcoverings	-	-	-	-
	EN 14904	-	-	-	Heterogeneous indoor sport floorcoverings			
Declaration of Performance	EN 14041	0120-003-DoP-2013-04	0120-006-DoP-2013-04	0120-026-DoP-2013-04	-	-	-	-
	EN 14904	-	-	-	0120-080-DoP-2018-11	0120-076-DoP-2017-10	0120-041-DoP-2013-04	0120-071-DoP-2016-04
TECHNICAL CHARACTERISTICS								
Total thickness	ISO 24346 (EN 428)	2mm	3.45mm	5mm	6.1mm	7.1mm	8.3mm	9.4mm
Total weight	ISO 23997 (EN 430)	3 045g/m ²	3 295g/m ²	4 080g/m ²	3950g/m ²	4795g/m ²	6 095g/m ²	6 200g/m ²
Width	ISO 24341 (EN 426)	2m	2m	2m	2m	2m	2m	2m
Length	ISO 24341 (EN 426)	231m	20.51m	20.51m	20.51m	20.51m	20.51m	20.51m
REQUIREMENTS FOR USE								
Shock absorption	Average measured value	-	≥ 4%	≥ 17%	P1	P1	P1	P2
	EN 14808 requirement	-	-	-	≥ 25%	≥ 25%	≥ 25%	≥ 35%
Friction	Average measured value	Compliant	Compliant	Compliant	Compliant	Compliant	Compliant	Compliant
	EN 13036-4 requirement	80 to 110	80 to 110	80 to 110	80 to 110	80 to 110	80 to 110	80 to 110
Vertical deformation	Average measured value	-	≤ 0.8mm	≤ 1mm	P1	P1	P1	P2
	EN 14809 requirement	-	≤ 5mm	≤ 5mm	≤ 2mm	≤ 2mm	≤ 2mm	≤ 3mm
TECHNICAL REQUIREMENTS								
Vertical ball behaviour	Average measured value	-	Compliant	Compliant	Compliant	Compliant	Compliant	Compliant
	EN 12235 requirement	-	≥ 90%	≥ 90%	≥ 90%	≥ 90%	≥ 90%	≥ 90%
Reaction to fire	EN 13501-1	B _{f1} s1*	C _{f1} s1*	C _{f1} s1*	C _{f1} s1**/***	C _{f1} s1**/***	C _{f1} s1**/***	C _{f1} s1**/***
Resistance to wear	EN ISO 5470-1	-	≤ 1g	≤ 1g	≤ 1g	≤ 1g	≤ 1g	≤ 1g
Resistance to indentation	Average measured value	-	≤ 0.18mm	≤ 0.16mm	≤ 0.10mm	≤ 0.15mm	≤ 0.15mm	Compliant
	EN 1516 requirement	-	≤ 0.50mm	≤ 0.50mm	≤ 0.50mm	≤ 0.50mm	≤ 0.50mm	≤ 0.50mm
Resistance to a rolling load	Average measured value	-	-	Compliant	Compliant	Compliant	Compliant	Compliant
	EN 1569 requirement	-	-	≤ 0.5mm	≤ 0.5mm	≤ 0.5mm	≤ 0.5mm	≤ 0.5mm
In room noise	NFS 31-074	-	Class A ≤ 65dB	Class A ≤ 65dB	Class A ≤ 65dB	Class A ≤ 65dB	Class A ≤ 65dB	Class A ≤ 65dB
Thermal resistance	EN ISO 10456	Approx. 0.02m ² K/W	Approx. 0.05m ² K/W	Approx. 0.07m ² K/W	Approx. 0.09m ² K/W	Approx. 0.10m ² K/W	Approx. 0.12m ² K/W	Approx. 0.14m ² K/W
ENVIRONMENTAL PERFORMANCES								
Total VOC emissions	ISO 16000-9	≤ 10µg/m ³ (after 28 days)	≤ 10µg/m ³ (after 28 days)	≤ 10µg/m ³ (after 28 days)	≤ 10µg/m ³ (after 28 days)	≤ 10µg/m ³ (after 28 days)	≤ 10µg/m ³ (after 28 days)	≤ 10µg/m ³ (after 28 days)
COLOURS								
		Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8

The above information is subject to modification for the benefit of further improvement. (12/18).
Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

*Glued installation **GreenLay installation

Compact

Speed

Training

Reference Multi-Use

Active

Excel

PurePlay

They certified Tarkett Omnisports

⁽¹⁾Available for Reference Multi-Use, Active, Excel & Pureplay

TARKETT SERVICE

TO MEET ALL OF YOUR EXPECTATIONS

TAILORED OFFER

Roll length on demand

Minimum quantity 550m² (on global order)*

Tarkett can handle your length requirement in order to give you and your project the personal attention to detail you deserve:

- Available by «multiple» of 10cm
- Waste reducing
- Time saving

NEW! CUT SERVICE

Flexible

Get the amount you really need.

- Available for all product profiles on stock rolls.
- Minimum quantity 1 roll.

CUSTOMIZED OFFER

Create your own color

Minimum quantity 800m² (+/-10% by colour)

Create your own colour based on other Tarkett collections or from RAL/ Pantone/ NCS proposal.

Leadtime 7 weeks

RESTART

Comprehensive collection and recycling service of flooring off-cuts.

- Optimizes jobsite waste management.
- Contributes to reducing jobsite waste.
- Guarantees traceability of collected off-cuts.
- Integrates sustainable development and anticipates European regulation requirements.



*Up to 5 weeks leadtime

■ **WESTERN EUROPE:** Austria: Tarkett Holding GmbH, Niederlassung Wien – Tel. +43 1 47 88 062 ■ **Belgium:** Tarkett Belux Sprl – Tel. +32 16 35 98 80 ■ **Denmark:** Tarkett A/S – Tel. +45 43 90 60 11
■ **Finland:** Tarkett Oy – Tel. +358 9 4257 9000 ■ **France:** Tarkett SAS – Tel. +33 1 41 20 42 49 ■ **Germany:** Tarkett Holding GmbH – Tel. +49 62 33 810 ■ **Greece:** Tarkett Monoprosopi Ltd –
Tel. +30 210 6745 340 ■ **Italy:** Tarkett S.p.A. – Tel. +39 0744 7551 ■ **Luxembourg:** Tarkett GDL SA – Tel. +352 949 211 8804 ■ **Netherlands:** Tarkett BV – Tel. +31 416 685 491 ■ **Norway:** Tarkett AS –
Tel. +47 32 20 92 00 ■ **Portugal:** Tarkett SA – Tel. +351 21 427 64 20 ■ **Spain:** Tarkett Floors S.L. – Tel. +34 91 358 00 35 ■ **Sweden:** Tarkett Sverige AB – Tel. +46 771 25 19 00 ■ **Switzerland:** Tarkett Holding
GmbH – Tel. +41 043 233 79 24 ■ **Turkey:** Tarkett Aspen - Tel. +90 212 213 65 80 ■ **United Kingdom:** Tarkett Ltd – Tel. +44 (0) 1622 854 040 ■ **EASTERN EUROPE:** Baltic Countries: Tarkett Baltics:
Tel. +370 37 262 220 ■ **Czech Republic:** Tarkett org. slozka – Tel. +420 271 001 600 ■ **Hungary:** Tarkett Polska SP Z.O.O. magyarországi fióktelepe – Tel. +36 1 437 8150 ■ **Poland:** Tarkett Polska
Sp. z o. o. – Tel. +48 22 16 09 231 ■ **Russian Federation:** ZAO Tarkett RUS - Tel. +7 495 775 3737 ■ **Slovakia:** Tarkett Polska, organizačná zložka – Tel. +421 2 48291 317 ■ **South East Europe:** Tarkett
SEE – Tel. +381 21 7557 649 (44) 569 12 21 ■ **Ukraine:** Tarkett UA – Tel. +38 (0) 44 569 12 21 ■ **ASIA AND OCEANIA:** Australia: Tarkett Australia Pty Ltd – Tel. +61 2 88 53 12 00 ■ **China:** Tarkett Floor
Covering (Shanghai) Co. Ltd. – Tel. +86 (21) 60 95 68 38 ext 841 ■ **North East Asia:** Tarkett Hong Kong Limited – Tel. +852 2511 8716 ■ **India:** Tarkett Flooring India Pvt. Ltd. – Bangalore -
Tel. +91 80 4130 3793 – New Delhi - Tel. +91 11 4352 4073 – Mumbai - Tel. +91 22 2648 8750 ■ **South East Asia:** Tarkett Flooring Singapore Pte. Ltd. – Tel. +65 6346 1585 ■ **AFRICA:** Tarkett International:
Tel. +33 1 41 20 41 01 ■ **MIDDLE EAST:** Tarkett Middle East: Tel. +961 1 51 3363/4 ■ **Israël:** Tarkett International: Tel. +33 1 41 20 41 01 ■ **NORTH AMERICA:** USA: Tarkett Inc. – Tel. +1 713 869 5811
/ Johnsonite – Tel. +1 440 543 8916 ■ **Canada:** Tarkett Inc. – Tel. +1 450 293 173 ■ **LATIN AMERICA:** Brazil: Tarkett - Tel. 55 12 3954 7108 ■ **Argentina - Chile - Uruguay:** Tarkett Latam Mercosur -
Tel. +54 11 47 08 07 72 / +54 9 11 44 46 88 82 ■ **Bolivia - Colombia - Ecuador - Panama - Paraguay - Peru - Trinidad and Tobago - Venezuela:** Tarkett - Tel. +55 11 9 8410 9310 / +55 11 95494 0069
■ **Mexico /Central America:** Tarkett Latam Mexico - Tel. +55 11 98410 9310.